

OSPL TPHZ51-B TEMPEST desktop laser projector

SDIP-27 Level B

SONY



Based on Sony PHZ51

Description and typical configuration	
Technology	3LCD system, laser diode light source
Native Resolution	Max signal resolution: 1920 x 1200 (4k/30p, 3840 x 2160 acceptable)
Compatibility	NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p, 4k/30p, 4k/25p, 4k/24p (4k means 3840)
Brightness	5300 lumens
Contrast ratio	Full white/Full black ∞:1
Image size	1.02m to 7.62m (diagonally)
Zoom type	Manual, (Approx. x 1.6)
Aspect ratio	16:10 (WUXGA)
Standards	Conference rooms, classrooms, visual simulation environments
Colours	1.07BN colour palette, 10-bits
Power	TEMPEST filtered AC input 100-240VAC- auto sense. C/w 1.8M shielded mains cable with country specific plug
Interface	1x HDMI port with optional Lindy 38170 HDMI fibre optic extender
Misc	IR Remote control, Lens cover
Options and upgrades	
Interface	5m shielded HDMI cable
Mounting	Ceiling mount
Country kit	Country specific main plugs/adapters
Warranty	1-year RTB warranty – excludes lamp